

The MODIS Conversion Toolkit (MCTK) User's Guide

Devin Alan White

Technical Support Engineer / Instructor
ITT Visual Information Solutions
dwhite@ittvis.com

Table of Contents

I.	Introduction.....	2
II.	Installation.....	2
III.	Converting MODIS data interactively in ENVI using MCTK.....	3
	A. Level 1A Uncalibrated Radiance.....	4
	B. Level 1B Calibrated Radiance.....	5
	C. Level 2 Swath.....	6
	D. Level 2/3/4 Grid.....	7
IV.	Converting MODIS data programmatically in ENVI using MCTK.....	10
	A. API calling syntax.....	11
	B. Examples.....	15
V.	Supported MODIS products.....	19
VI.	MODIS Conversion Toolkit Processing Workflow Diagram.....	25

I. Introduction

The MODIS Conversion Toolkit (MCTK) is an HDF file conversion and projection utility for all known MODIS data products. The plugin works on all operating systems that can run IDL and ENVI. A complete list of supported products can be found in Section V. MCTK allows you to take a cafeteria-style approach to working with MODIS data. Through an intuitive user interface, you can extract and project only the data you need. Full programmatic access to MCTK is also available (see Section IV for details).

II. Installation

To install MCTK, place the “modis_conversion_toolkit.sav” file in your ENVI save_add folder. The location of this folder will vary by operating system:

Windows: c:\rsi\idl63\products\envi43\save_add

UNIX/Linux: /usr/local/rsi/idl_6.3/products/envi_4.3/save_add

Mac: /applications/rsi/idl_6.3/products/envi_4.3/save_add

If the plugin is installed correctly, there should be a MODIS Conversion Toolkit button in the ENVI menu system under File→Open External File→EOS the next time ENVI is started (Figure 1).




Figure 1. The plugin creates a button in the EOS group in ENVI, allowing for easy access to data sets.

III. Converting MODIS data interactively in ENVI using MCTK

To bring a MODIS file into MCTK, launch the tool from the Open External File menu and in the resulting window, click on Input HDF, and select the file you wish to input. By design, a file filter is preset so that only files that begin with “M” and have an “.hdf” suffix will be displayed in the file selection dialog. Only one file can be selected at a time for conversion. It is crucial that the name of your input file follows standard MODIS naming convention. The tool uses the first part of the file name (e.g., MOD02HKM) to determine the product type and appropriate processing options. The best way to ensure compliance with the naming convention is to retain the filenames assigned by your data provider. When a valid MODIS product is supplied to the tool, the various fields in the window will update (Figure 2). Directly below the Input HDF button is a field that will display metadata related to the inputted file. Georeferencing options for converted data will appear directly below the metadata viewer, when appropriate. The Processing Options area on the right side will provide you with an interactive list of what can be done with the inputted data. This list is different for every product. If georeferencing options are available for the inputted product, and one of them is chosen, the window will expand to include a section that gives you control over several parameters including projection type, resampling method, density of the triangulation grid (warp points), bow tie correction, and pixel size (when appropriate).




Figure 2. A “blank” instance of MCTK. The various fields and sections will update with information and options that are relevant to the supplied MODIS product. To ensure that you have the most recent version of MCTK, check the displayed Build Date.

To select where converted data should be placed, click on the Output Path button and select a folder. The folder where the input file resides is chosen by default. You must also provide a rootname for the outputted data. The string value you choose will be used as the first part of longer filenames automatically built by the tool during the conversion process. Since multiple

files can be generated by a single conversion process, it is useful to choose an intuitive and descriptive rootname so data from the same input file can be easily grouped afterwards.

A. Level 1A Uncalibrated Radiance

When a Level 1A Uncalibrated Radiance file is provided as input, you will be presented with several processing options. On the right side, you will see the four datasets stored inside of the HDF that contain image data at three spatial resolutions (250m, 500m, and 1000m). MCTK recognizes the fact that there are multiple resolutions within the file and displays them in the metadata window under Pixel Size. You can choose to output any combination of the available datasets, but each will be placed in a separate file due to how they are processed by the tool. Each output file will contain appropriate band number designations and wavelength values. After clicking on Process, you will see two ENVI progress bars: one related to the conversion of the current dataset and one related to the overall conversion process.

The tool also recognizes that Level 1A data does not contain georeferencing information (indicated by the Native Projection being set to None in the metadata viewer). However, if you have access to the related Geolocation product (MOD03/MYD03), you can use it to project the Level 1A data. To do so, select Projected or Standard and Projected under Output Type and then click on Input Geolocation File. You will be prompted to supply an appropriate file. A filter is provided to aid you in finding the correct product and the current Level 1A filename will show up in the title bar of the file selection dialog. In order to proceed, the second, third and fourth sections of the Level 1A filename and geolocation filename have to match. For example, a Level 1A file with the name "MYD01.A2006007.0300.005.2007078081622.hdf" requires a geolocation file with the name "MYD03.A2006007.0300.005.2006125230829.hdf." If the supplied filenames do not match, the projection options section will be greyed out and you will not be allowed to proceed with the conversion. If the filenames do match, the most appropriate UTM zone for the supplied data is automatically calculated and made available (Figure 3). Standard resampling methods (Nearest Neighbor, Bilinear, and Cubic Convolution) are available, as is Bow Tie Correction. If the latter is chosen, the former set of methods become inaccessible since only one can be used during projection. The number of warp points to use is set to 50 x 50 by default, which results in 2500 GCPs distributed evenly across the entire scene. While this should be more than enough to carry out an accurate triangulation warp, you can choose to use more or less points. This option is also not available when Bow Tie Correction is chosen due to differences in how this method uses the supplied geolocation file. Output pixel size is automatically determined based on product type and dataset. For projections that do not use meters, the meter-based pixel size is automatically converted to one that is appropriate. You also have the option of providing your own background value to use during the projection process. The default value is 0. If a value less than zero is provided, zero is used instead.

Filenames for converted data

For Level 1A files, two types of filenames are possible. They are constructed as follows:

- Rootname + Dataset Name + Raw_DN.img (unprojected data)
- Rootname + Dataset Name + Raw_DN_georef.img (projected data)

A Note on Output Type

Because MCTK is a conversion utility, you will always receive at least one ENVI format file as output. If you choose to output projected data using the Projected or Standard and Projected

option, two sets of output files will be generated. The first set is unprojected (Standard) and is used to create the second set (Projected). The difference between the two options is that when you choose Projected, the first set of files (Standard) is deleted once the projection process is complete.

A Note on Using Bow Tie Correction with 250m Data

In order to use Bow Tie Correction with 250m data, you must change your Image Tile Size in the ENVI Preferences dialog (under Miscellaneous) to a value of at least 5.0 MB. If this is not done, you will likely receive an error message stating that the interpolation method did not have enough data to successfully carry out the correction.




Figure 3. MCTK with a Level 1A file supplied as input, along with a matching geolocation file.

B. Level 1B Calibrated Radiance

When a Level 1B Calibrated Radiance file is provided as input, you will be presented with several processing options that will vary depending on the product you are working with. In all cases, you will have the option to output projected data using the internal 1km-resolution geolocation fields in a fashion similar to that for Level 1A data (see above discussion). You do not need to supply a matching MOD03/MYD03 geolocation file. For a MOD02QKM file there is only one possible dataset to select for output, but multiple datasets are available for MOD02HKM, MOD021KM, and MOD02SSH. Output will always be consolidated into one file (before projection takes place) due to the fact that the spatial resolutions are the same for each dataset within a file. Appropriate band numbers and wavelengths will be attached to the output file as well. If you want to use Bow Tie Correction on MOD02QKM data, please refer to the above note regarding that correction method and 250m data. Apart from georeferencing and dataset selection options, MCTK also gives you the ability to choose which type of calibration to

perform on the stored data: radiance & emissivity or TOA reflectance & emissivity (Figure 4). Radiance is returned in units of $W/m_2/\mu m/sr$, reflectance is returned as unitless values between 0.0 and 1.0. Calibration for emissivity data is only carried out on 1km products that contain an emissive dataset. You also have the option of providing your own background value to use during the projection process, which can be specified as an integer or floating point. The default value is NaN (not a number).

Filenames for converted data

For Level 1B files, two types of filenames are possible. They are constructed as follows:

- Rootname + Calibration Method + .img (unprojected data)
- Rootname + Calibration Method + georef.img (projected data)




Figure 4. MCTK with a Level 1B file supplied as input (MOD021KM). Multiple datasets have been selected for georeferenced output, Reflectance / Emissivity has been chosen as the calibration method, and Bow Tie Correction has been turned on.

C. Level 2 Swath

When a Level 2 Swath file is provided as input, the available output options will be very similar to those for Level 1B files. However, there are a few important exceptions related to available datasets and converted output. As with Level 1A/B files, you will be presented with a list of datasets contained within the file that can be processed. The list is determined by scanning all datasets present in the file and determining which ones contain data that are stored in at least two dimensions (Figure 5). The dimensionality of each dataset appears to the left of the dataset name in the list (2D or 3D). If scale and offset factors are present for a particular dataset, they are automatically applied during the conversion process. Depending on the datasets chosen

and the number of spatial resolutions present, you may receive multiple output files. Datasets are grouped by spatial resolution and dimensionality prior to processing. For example, if you are working with MOD05_L2 (Precipitable Water), datasets exist at both 1000m and 5000m spatial resolutions and in two and three dimensions. All two dimensional data at 1000m are grouped into one multiband output file, where each band name is the name of an individual dataset. Each three dimensional dataset at 1000m receives its own output file. The process is then repeated for 5000m datasets. The filenames automatically generated by MCTK will reflect this process. You also have the option of providing your own background value to use during the projection process, which can be specified as an integer or floating point. The default value is NaN (not a number).

Filenames for converted data

For Level 2 Swath files, two types of filenames are possible. They are constructed as follows:

- Rootname + Swath + Dimensionality + Resolution Index + Output File Number + .img (unprojected data)
- Rootname + Swath + Dimensionality + Resolution Index + Output File Number + georef.img (projected data)

where Dimensionality will be 2D or 3D, Resolution Index is an incremented value from 1 to the total number of spatial resolutions present (starting with the highest resolution), and Output File Number is an incremented value from 1 to the total number of files outputted for a particular dimensionality within a particular spatial resolution. There is currently no way within MCTK to tell which datasets will map to a particular spatial resolution prior to starting the conversion process.




Figure 5. MCTK with a Level 2 Swath file supplied as input. Multiple datasets with different dimensionalities and spatial resolutions have been selected for processing.

D. Level 2/3/4 Grid

When a Level 2G, Level 3 or Level 4 Grid file is provided as input, you may encounter an additional dialog which will prompt you to select which grid to process (Figure 6). While the occurrence of multiple grids within a file is rare, it can happen.




Figure 6. When inputting a file that contains more than one grid, you will automatically be prompted to select which one to process.

Once a grid is selected, the output options are almost identical to those for Level 2 Swath data. There are two major differences. First, grid data are already projected, so Standard output will use the native map information stored in the HDF file (usually Sinusoidal or Geographic Lat/Lon, but EASE Grid is also supported for NSIDC datasets). As a result of this fact, the usual Projected option is listed as Reprojected and gives you the chance to put your data in another map projection. This is a common practice with Sinusoidal data, which is generally put into Geographic Lat/Lon or UTM. When the Reprojected option is chosen, the map projection output options will show up with Geographic Lat/Lon chosen by default (Figure 7). A default output pixel size (in degrees) is also automatically calculated in the appropriate units, based on the input pixel size for the product (usually meters). Note that if the grid's native projection is Geographic Lat/Lon, that projection is still the default Reprojection option. Choosing to reproject using the default values in this case will essentially create the same output as choosing Standard. A useful thing to do in this situation, since most Geographic Lat/Lon data is global in scale, would be to choose a larger output pixel size, which in essence shrinks the size of the resulting output file but retains the same projection as the original input. You also have the option of providing your own background value to use during the reprojection process, which can be specified as an integer or floating point. The default value is NaN (not a number).




Figure 7. MCTK with a Level 4 Grid file supplied as input. Multiple datasets with different dimensionalities have been selected for processing and the reprojection option is set for Geographic Lat/Lon.

Filenames for converted data

For Level 2G, Level 3 and Level 4 Grid files, four types of filenames are possible. They are constructed as follows:

- Rootname + Grid + Dimensionality + Output File Number + .img (unprojected 2D or 3D data)
- Rootname + Swath + Dimensionality + Output File Number + reprojected.img (projected 2D or 3D data)
- Rootname + Grid + Dimensionality + Dataset Index + Dimension Index + .img (unprojected 4D data)
- Rootname + Swath + Dimensionality + Dataset Index + Dimension Index + reprojected.img (projected 4D data)

where Dimensionality will be 2D, 3D, or 4D; Dimension Index is an incremented value from 1 to the total number of “bands” in the fourth dimension (each one maps to a 3D data cube); Output File Number is an incremented value from 1 to the total number of files outputted for 2D and 3D datasets; and Dataset Index is an incremented value from 1 to the total number of 4D datasets chosen for output. The naming convention for 4D output is potentially headache-inducing due to the complexities of the HDF file structure for that type of data, so an example would be as follows. If you inputted a MOD43B3 file, selected both the 4D “Albedo” dataset and 3D “Albedo_Quality” dataset for conversion, provided “albedo” as your rootname, and opted to reproject the converted data, the resulting files would look like this:

albedo_Grid_4D_1_1_reprojected.img (first 4D dataset, first 3D cube of data)
 albedo_Grid_4D_1_2_reprojected.img (first 4D dataset, second 3D cube of data)

albedo_Grid_3D_1_reprojected.img (first 3D dataset)

Since ENVI cannot handle 4D datasets, they are broken down into more manageable 3D cubes. In this example, the original 4D dataset had dimensions of 1200x1200x10x2, so two 3D datasets were generated—each one consisting of a 1200x1200x10 cube. A 4D dataset with dimensions of 1200x1200x10x20 would result in 20 3D cubes (and 20 output files).

IV. Converting MODIS data programmatically in ENVI using MCTK

All of MCTK's functionality is programmatically available. The interactive version is simply a way to gather information about the inputted file and assist the user with selecting the data they want to output and how the output should be handled. Once all of this information is collected by the widget, it is handed off to the same processing routine discussed here (CONVERT_MODIS_DATA). The processing routine can be called like any other IDL procedure as long as `convert_modis_data.sav` is in your ENVI `save_add` folder. There are many keywords associated with the procedure, but not all of them are required for every type of MODIS data. Consult the keyword definitions and example programs on the following pages to determine which ones you will need to use. Multiple file conversion must be carried out one file at a time, so running `CONVERT_MODIS_DATA` on multiple files will require the construction of a FOR loop that passes each file of interest into the routine sequentially.

CONVERT_MODIS_DATA

Syntax

```
CONVERT_MODIS_DATA [,IN_FILE=string] [,OUT_PATH=string] [,OUT_ROOT=string]
[,/L1A] [,/L1B] [,/MOD14] [,/HIGHER_PRODUCT] [,/SWATH] [,/GRID]
[,SWT_NAME=string] [,GD_NAME=string] [,SD_NAMES=string array]
[,OUT_METHOD={0 | 1 | 2}] [,GEOLOC_FILE=string] [,OUT_PROJ=envi projection
structure] [,OUT_PS_X=double] [,OUT_PS_Y=double] [,NUM_X_PTS=integer]
[,NUM_Y_PTS=integer] [,INTERP_METHOD={6 | 7 | 8}] [,/BOWTIE]
[,CALIB_METHOD={0 | 1}] [,SD_POS=integer array] [,/NO_MSG]
[,BACKGROUND=integer or float]
```

Keywords

IN_FILE

Use this keyword to specify the name and path of the MODIS file. IN_FILE is a string variable that ENVI will use to open the MODIS file for reading.

OUT_PATH

Use this keyword to specify a string with the output path for the resulting converted data. The specified string must end with the appropriate path separation character for your operating system (“\” for Windows, “/” for UNIX, Linux, and Mac).

OUT_ROOT

Use this keyword to specify a string that will be used in building filenames for the resulting converted data. The specified value will appear at the beginning of generated filenames.

/L1A (optional)

Set this keyword to indicate that a Level 1A Uncalibrated Radiance file will be provided as input.

/L1B (optional)

Set this keyword to indicate that a Level 1B Calibrated Radiance file will be provided as input.

/HIGHER_PRODUCT (optional)

Set this keyword to indicate that a Level 2, Level 3, or Level 4 product will be provided as input.

/MOD14 (optional)

Set this keyword to indicate that a MOD14/MYD14 file will be provided as input. Note: It is not currently possible to project this product, so OUT_METHOD must be set to 0. This keyword is ignored unless the /HIGHER_PRODUCT keyword is set.

/SWATH (optional)

Set this keyword to indicate that the file specified by IN_FILE contains data in EOS Swath format. This keyword is ignored if the /L1A keyword or /L1B keyword is set.

/GRID (optional)

Set this keyword to indicate that the file specified by IN_FILE contains data in EOS Grid format. This keyword is ignored if the /L1A keyword or /L1B keyword is set.

SWT_NAME (optional)

Use this keyword to specify a string that contains the exact name of the EOS swath from which data will be extracted (it is also case sensitive). This keyword is ignored unless the /HIGHER_PRODUCT and /SWATH keywords are set.

GD_NAME (optional)

Use this keyword to specify a string that contains the exact name of the EOS grid from which data will be extracted (it is also case sensitive). This keyword is ignored unless the /HIGHER_PRODUCT and /GRID keywords are set.

SD_NAMES (optional)

Use this keyword to specify a string array that contains the exact names of the datasets to extract from the provided MODIS file (it is also case sensitive). This keyword is ignored unless the /HIGHER_PRODUCT keyword is set.

OUT_METHOD (optional)

Set this keyword to one of the following values to specify the output method to use when converting data.

- 0 — Standard (no projection/reprojection is carried out, one set of output files)
- 1 — Projected (user-supplied projection/reprojection is carried out, one set of output files)
- 2 — Standard and Projected (two sets of output files)

GEOLOC_FILE (optional)

Use this keyword to specify the name and path of the MODIS Geolocation file (MOD03/MYD03) you will use for projecting Level 1A data. This keyword is ignored unless the /L1A keyword is set.

OUT_PROJ (optional)

Use this keyword to specify the map projection to use when projecting/reprojecting data. OUT_PROJ is a projection structure returned from ENVI_GET_PROJECTION or ENVI_PROJ_CREATE.

OUT_PS_X (optional)

Set this keyword to a double-precision value containing the X pixel size of the output image. You should specify the pixel size in the units contained in the projection structure passed to the OUT_PROJ keyword. This keyword is ignored unless the /GRID keyword is set.

OUT_PS_Y (optional)

Set this keyword to a double-precision value containing the Y pixel size of the output image. You should specify the pixel size in the units contained in the projection structure passed to the OUT_PROJ keyword. This keyword is ignored unless the /GRID keyword is set.

NUM_X_PTS (optional)

Use this keyword to specify the number of points to use in the X direction when building the grid of ground control points used for image projection/reprojection. A suggested value would be 50. This keyword is ignored if /BOWTIE is set.

NUM_Y_PTS (optional)

Use this keyword to specify the number of points to use in the Y direction when building the grid of ground control points used for image projection/reprojection. A suggested value would be 50. This keyword is ignored if /BOWTIE is set.

/BOWTIE (optional)

Set this keyword to use Bow Tie Correction during the process of projecting Level 1 and Level 2 Swath data. If this keyword is not set, traditional triangulation-based Image to Map Registration is used during the projection process through the INTERP_METHOD keyword.

CALIB_METHOD (optional)

Set this keyword to one of the following values to specify which calibration method to use when converting Level 1B Radiance data.

- 0 — Radiance / Emissivity
- 1 — Reflectance / Emissivity

This keyword is ignored unless the /L1B keyword is set as well.

SD_POS (optional)

Use this keyword to specify which datasets within a Level 1A Uncalibrated Radiance file or Level 1B Calibrated Radiance file to process. The datasets are specified by providing an integer array to the procedure using the following positional values, which are different for each spatial resolution.

Product: MOD01 / MYD01 (250m, 500m, 1000m)
Datasets: EV_250m, EV_500m, EV_1km_day, EV_1km_night
Array: [0, 1, 2, 3]

Product: MOD02QKM / MYD02QKM (250m)
Datasets: EV_250_RefSB
Array: [0]

Product: MOD02HKM / MYD02HKM (500m)
Datasets: EV_250_Aggr500_RefSB, EV_500_RefSB
Array: [0, 1]

Product: MOD021KM / MYD021KM (1000m)
Datasets: EV_250_Aggr1km_RefSB, EV_500_Aggr1km_RefSB,
 EV_1KM_RefSB, EV_1KM_Emissive
Array: [0, 1, 2, 3]

Product: MOD02SSH / MYD02SSH (5000m)
Datasets: EV_250_Aggr1km_RefSB, EV_500_Aggr1km_RefSB,
 EV_1KM_RefSB, EV_1KM_Emissive
Array: [0, 1, 2, 3]

For example, to process only the “EV_500_Aggr1km_RefSB” and “EV_1KM_Emissive” datasets for a MOD021KM file, the array would be [1, 3]. NOTE: array values *must* be specified in ascending order from left to right. This keyword is ignored unless the /L1A keyword or /L1B keyword is set.

INTERP_METHOD (optional)

Set this keyword to one of the following values to specify the resampling method to use with the triangulation-based projection/reprojection process.

- 6 — Nearest neighbor
- 7 — Bilinear
- 8 — Cubic convolution

This keyword is ignored if /BOWTIE is set.

/NO_MSG (optional)

Set this keyword to suppress the display of the lat/lon geofields interpolation status window during the swath projection process. Window suppression is useful when processing large numbers of files in non-interactive batch mode. This keyword is ignored unless the /L1A keyword, /L1B keyword, or /SWATH keyword is set.

BACKGROUND (optional)

Use this keyword to specify the value for all background pixels that result from a projection or reprojection process. The default is 0 for Level 1A and NaN for all other products. The value can be specified as an integer or floating point number. If a value less than zero is supplied for Level 1A data, zero will be used instead.

EXAMPLES

```
;Level 1A example
pro test_batch_modis_conversion_level_1a
    compile_opt idl2

    modis_l1a_file = 'C:\MYD01.A2006007.0300.005.2007078081622.hdf'

    ;The specified output location MUST end in the appropriate path
    ;separator for your OS
    output_location = 'C:\MCTK_Output\'

    output_rootname = 'level_1a'

    ;Output method schema is:
    ;0 = Standard, 1 = Projected, 2 = Standard and Projected
    out_method = 1

    ;Specify MOD03/MYD03 file to use for georeferencing
    geoloc_file = 'C:\MYD03.A2006007.0300.005.2006125230829.hdf'

    output_projection = envi_proj_create(/geographic)

    ;The interp method keyword uses the same numbering scheme as
    ;ENVI_REGISTER_DOIT's METHOD keyword
```

```

;Choosing Triangulation with Nearest Neighbor. This keyword is ignored
;if /bowtie is set.
interpolation_method = 6

;Setting num_x_pts to 50 and num_y_pts to 50 results in 2500 GCPs.
;That should be more than enough....
;These keywords are ignored if /bowtie is set.
convert_modis_data, in_file=modis_l1a_file, out_path=output_location, $
    out_root=output_rootname, /l1a, out_method=out_method, $
    geoloc_file=geoloc_file, out_proj=output_projection, $
    num_x_pts=50, num_y_pts=50, interp_method=interpolation_method, $
    sd_pos=[0,1,2,3], /no_msg
end

;Level 1B example
pro test_batch_modis_conversion_level_1b
    compile_opt idl2

    modis_l1b_file = 'C:\MOD021KM.A2007079.0855.005.2007079160027.hdf'

    ;The specified output location MUST end in the appropriate path
    ;separator for your OS
    output_location = 'C:\MCTK_Output\'

    output_rootname = 'level_1b'

    ;Calibration method schema is:
    ;0 = Radiance \ Emissivity, 1 = Reflectance \ Emissivity
    calib_method = 1

    ;Output method schema is:
    ;0 = Standard, 1 = Projected, 2 = Standard and Projected
    out_method = 1

    output_projection = envi_proj_create(/geographic)

    ;Use bow tie correction during the projection process
    convert_modis_data, in_file=modis_l1b_file, out_path=output_location, $
        out_root=output_rootname, /l1b, out_method=out_method, $
        out_proj=output_projection, calib_method=calib_method, /bowtie, $
        sd_pos=[1,3], /no_msg, background=0.0
end

;MOD14 example
pro test_batch_modis_conversion_mod14
    compile_opt idl2

    modis_mod14_file = 'C:\MOD14.A2007075.0030.005.2007075053706.hdf'

    ;The specified output location MUST end in the appropriate path
    ;separator for your OS
    output_location = 'C:\MCTK_Output\'

    output_rootname = 'fire_mask'

    sd_names = ['fire mask', 'algorithm QA']

    ;Since MOD14/MYD14 files have corrupted geofields, georeferencing is
    ;not possible with this product. All related keywords are ignored
    ;except out_method, which must be set to 0.
    out_method = 0

```

```

convert_modis_data, in_file=modis_mod14_file, $
    out_path=output_location, out_root=output_rootname, /mod14, $
    /higher_product, sd_names=sd_names, out_method=out_method
end

;Level 2 swath example
pro test_batch_modis_conversion_l2_swath
    compile_opt idl2

    modis_swath_file = 'C:\MOD05_L2.A2004026.0110.004.2004028152013.hdf'

    ;The specified output location MUST end in the appropriate path
    ;separator for your OS
    output_location = 'C:\MCTK_Output\'

    output_rootname = 'water_vapor'

    swath_name = 'mod05'

    sd_names = ['Water_Vapor_Near_Infrared', 'Water_Vapor_Infrared']

    ;Output method schema is:
    ;0 = Standard, 1 = Projected, 2 = Standard and Projected
    out_method = 1

    output_projection = envi_proj_create(/geographic)

    ;The interp_method keyword uses the same numbering scheme as
    ;ENVI_REGISTER_DOIT's METHOD keyword
    ;Choosing Triangulation with Nearest Neighbor. This keyword is ignored
    ;if /bowtie is set
    interpolation_method = 6

    ;Setting num_x_pts to 50 and num_y_pts to 50 results in 2500 GCPs.
    ;That should be more than enough....
    ;These keywords are ignored if /bowtie is set
    convert_modis_data, in_file=modis_swath_file, $
        out_path=output_location, out_root=output_rootname, $
        /higher_product, /swath, swt_name=swath_name, $
        sd_names=sd_names, out_method=out_method,
        out_proj=output_projection, num_x_pts=50, num_y_pts=50,
        interp_method=interpolation_method, /no_msg
end

;Level 3 grid example
pro test_batch_modis_conversion_grid
    compile_opt idl2

    modis_grid_file = 'C:\MOD13A3.A2004061.h10v06.004.2004110184849.hdf'

    ;The specified output location MUST end in the appropriate path
    ;separator for your OS
    output_location = 'C:\MCTK_Output\'

    output_rootname = 'monthly_NDVI'

    grid_name = 'MOD_Grid_monthly_1km_VI'

    sd_names = ['1 km monthly NDVI', '1 km monthly EVI']

    ;Output method schema is:

```

```

;0 = Standard, 1 = Reprojected, 2 = Standard and reprojected
out_method = 1

output_projection = envi_proj_create(/geographic)

;Specify the output X and Y pixel sizes in double precision floating
;point. Sizes must be in units relevant to selected output projection
;(degrees in this example).
out_ps_x = 0.008370d
out_ps_y = 0.008370d

;The interp_method keyword uses the same numbering scheme as
;ENVI_REGISTER_DOIT's METHOD keyword
;Choosing Triangulation with Nearest Neighbor.
interpolation_method = 6

;Setting num_x_pts to 50 and num_y_pts to 50 results in 2500 GCPs.
;That should be more than enough....
convert_modis_data, in_file=modis_grid_file, $
    out_path=output_location, out_root=output_rootname, $
    /higher_product, /grid, gd_name=grid_name, sd_names=sd_names, $
    out_method=out_method, out_proj=output_projection, $
    out_ps_x=out_ps_x, out_ps_y=out_ps_y, num_x_pts=50, $
    num_y_pts=50, interp_method=interpolation_method, $
    background=-999
end

```

V. Supported MODIS Products

Product	Level	Type	GSD (m or deg)	Product Name	Group	Supported
MOD01	1	S	250-1000	Level 1A Radiance - Terra	Calibration	Yes
MYD01	1	S	250-1000	Level 1A Radiance - Aqua	Calibration	Yes
MOD021KM	1	S	1000	Level 1B Calibrated Radiance 1km - Terra	Calibration	Yes
MYD021KM	1	S	1000	Level 1B Calibrated Radiance 1km - Aqua	Calibration	Yes
MOD02HKM	1	S	500	Level 1B Calibrated Radiance 500m - Terra	Calibration	Yes
MYD02HKM	1	S	500	Level 1B Calibrated Radiance 500m - Aqua	Calibration	Yes
MOD02QKM	1	S	250	Level 1B Calibrated Radiance 250m - Terra	Calibration	Yes
MYD02QKM	1	S	250	Level 1B Calibrated Radiance 250m - Aqua	Calibration	Yes
MOD02OBC	1	S	N/A	Level 1B On-Board Calibrator - Terra	Calibration	No
MYD01OBC	1	S	N/A	Level 1B On-Board Calibrator - Aqua	Calibration	No
MOD02SSH	1	S	5000	Level 1B Calibrated Radiance 5km - Terra	Calibration	Yes
MYD02SSH	1	S	5000	Level 1B Calibrated Radiance 5km - Aqua	Calibration	Yes
MOD03	1	S	1000	Geolocation Fields 1km - Terra	Calibration	Yes
MYD03	1	S	1000	Geolocation Fields 1km - Aqua	Calibration	Yes
MOD04_L2	2	S	1000	Aerosol Product - Terra	Atmosphere	Yes
MYD04_L2	2	S	1000	Aerosol Product - Aqua	Atmosphere	Yes
MOD05_L2	2	S	1000 or 5000	Precipitable Water - Terra	Atmosphere	Yes
MYD05_L2	2	S	1000 or 5000	Precipitable Water - Aqua	Atmosphere	Yes
MOD06_L2	2	S	1000	Cloud Product - Terra	Atmosphere	Yes
MYD06_L2	2	S	1000	Cloud Product - Aqua	Atmosphere	Yes
MOD07_L2	2	S	1000	Atmospheric Profile - Terra	Atmosphere	Yes
MYD07_L2	2	S	1000	Atmospheric Profile - Aqua	Atmosphere	Yes
MOD35_L2	2	S	250 or 1000	Cloud Mask - Terra	Atmosphere	Yes
MYD35_L2	2	S	250 or 1000	Cloud Mask - Aqua	Atmosphere	Yes
MODATML2	2	S	5000 or 10000	Atmosphere Joint Product - Terra	Atmosphere	Yes
MYDATML2	2	S	5000 or 10000	Atmosphere Joint Product - Aqua	Atmosphere	Yes
MOD08_D3	3	G	1	Atmosphere Daily Global Product - Terra	Atmosphere	Yes
MYD08_D3	3	G	1	Atmosphere Daily Global Product - Aqua	Atmosphere	Yes
MOD08_E3	3	G	1	Atmosphere Eight-Day Global Product - Terra	Atmosphere	Yes
MYD08_E3	3	G	1	Atmosphere Eight-Day Global Product - Aqua	Atmosphere	Yes
MOD08_M3	3	G	1	Atmosphere Monthly Global Product - Terra	Atmosphere	Yes
MYD08_M3	3	G	1	Atmosphere Monthly Global Product - Aqua	Atmosphere	Yes
MOD09GQ	2G	G	250	Surface Reflectance Daily L2G Global 250m - Terra	Land	Yes
MYD09GQ	2G	G	250	Surface Reflectance Daily L2G Global 250m - Aqua	Land	Yes

The MODIS Conversion Toolkit User's Guide

MOD09GA	2G	G	500 or 1000	MODIS/Terra Surface Reflectance Daily L2G Global 1km and 500m SIN Grid	Land	Yes
MYD09GA	2G	G	500 or 1000	MODIS/Aqua Surface Reflectance Daily L2G Global 1km and 500m SIN Grid	Land	Yes
MOD09CMG	3	G	0.05	Surface Reflectance Daily L3 Global 0.05Deg CMG - Terra	Land	Yes
MYD09CMG	3	G	0.05	Surface Reflectance Daily L3 Global 0.05Deg CMG - Aqua	Land	Yes
MOD09A1	3	G	500	Surface Reflectance 8-Day L3 Global 500m - Terra	Land	Yes
MYD09A1	3	G	500	Surface Reflectance 8-Day L3 Global 500m - Aqua	Land	Yes
MOD09Q1	3	G	250	Surface Reflectance 8-Day L3 Global 250m - Terra	Land	Yes
MYD09Q1	3	G	250	Surface Reflectance 8-Day L3 Global 250m - Aqua	Land	Yes
MOD09GHK	2G	G	500	Surface Reflectance Daily L2G Global 500m - Terra	Land	Yes
MYD09GHK	2G	G	500	Surface Reflectance Daily L2G Global 500m - Aqua	Land	Yes
MOD09GQK	2G	G	250	Surface Reflectance Daily L2G Global 250m - Terra	Land	Yes
MYD09GQK	2G	G	250	Surface Reflectance Daily L2G Global 250m - Aqua	Land	Yes
MOD09GST	2G	G	1000	Surface Reflectance Quality Daily L2G - Terra	Land	Yes
MYD09GST	2G	G	1000	Surface Reflectance Quality Daily L2G - Aqua	Land	Yes
MOD11A1	3	G	1000	Land Surface Temperature/Emissivity Daily L3 Global 1km - Terra	Land	Yes
MYD11A1	3	G	1000	Land Surface Temperature/Emissivity Daily L3 Global 1km - Aqua	Land	Yes
MOD11A2	3	G	1000	Land Surface Temperature/Emissivity 8-Day L3 Global 1km - Terra	Land	Yes
MYD11A2	3	G	1000	Land Surface Temperature/Emissivity 8-Day L3 Global 1km - Aqua	Land	Yes
MOD11B1	3	G	5000	Land Surface Temperature/Emissivity Daily L3 Global 5km - Terra	Land	Yes
MYD11B1	3	G	5000	Land Surface Temperature/Emissivity Daily L3 Global 5km - Aqua	Land	Yes
MOD11_L2	2	S	1000	Land Surface Temperature/Emissivity Daily 5-Min L2 Swath 1km - Terra	Land	Yes
MYD11_L2	2	S	1000	Land Surface Temperature/Emissivity Daily 5-Min L2 Swath 1km - Aqua	Land	Yes
MOD11C1	3	G	0.05	Land Surface Temperature/Emissivity Daily L3 Global 0.05Deg CMG - Terra	Land	Yes
MYD11C1	3	G	0.05	Land Surface Temperature/Emissivity Daily L3 Global 0.05Deg CMG - Aqua	Land	Yes
MOD11C2	3	G	0.05	Land Surface Temperature/Emissivity 8-Day L3 Global 0.05Deg CMG - Terra	Land	Yes
MYD11C2	3	G	0.05	Land Surface Temperature/Emissivity 8-Day L3 Global 0.05Deg CMG - Aqua	Land	Yes
MOD11C3	3	G	0.05	Land Surface Temperature/Emissivity Monthly L3 Global 0.05Deg CMG - Terra	Land	Yes
MYD11C3	3	G	0.05	Land Surface Temperature/Emissivity Monthly L3 Global 0.05Deg CMG - Aqua	Land	Yes
MOD12C1	3	G	0.05	Land Cover Type Yearly L3 Global 0.05Deg CMG	Land	Yes
MOD12Q1	3	G	1000	Land Cover Type Yearly L3 Global 1km	Land	Yes
MOD12Q2	3	G	1000	Land Cover Dynamics Yearly L3 Global 1km	Land	Yes
MOD13Q1	3	G	250	Vegetation Indices 16-Day L3 Global 250m - Terra	Land	Yes
MYD13Q1	3	G	250	Vegetation Indices 16-Day L3 Global 250m - Aqua	Land	Yes
MOD13A1	3	G	500	Vegetation Indices 16-Day L3 Global 500m - Terra	Land	Yes
MYD13A1	3	G	500	Vegetation Indices 16-Day L3 Global 500m - Aqua	Land	Yes
MOD13A2	3	G	1000	Vegetation Indices 16-Day L3 Global 1km - Terra	Land	Yes

The MODIS Conversion Toolkit User's Guide

MYD13A2	3	G	1000	Vegetation Indices 16-Day L3 Global 1km - Aqua	Land	Yes
MOD13A3	3	G	1000	Vegetation Indices Monthly L3 Global 1km - Terra	Land	Yes
MYD13A3	3	G	1000	Vegetation Indices Monthly L3 Global 1km - Aqua	Land	Yes
MOD13C1	3	G	0.05	Vegetation Indices 16-Day L3 Global 0.05Deg CMG - Terra	Land	Yes
MYD13C1	3	G	0.05	Vegetation Indices 16-Day L3 Global 0.05Deg CMG - Aqua	Land	Yes
MOD13C2	3	G	0.05	Vegetation Indices Monthly L3 Global 0.05Deg CMG - Terra	Land	Yes
MYD13C2	3	G	0.05	Vegetation Indices Monthly L3 Global 0.05Deg CMG - Aqua	Land	Yes
MOD14	2	S	1000	Thermal Anomalies/Fire 5-Min L2 Swath 1km - Terra	Land	Yes
MYD14	2	S	1000	Thermal Anomalies/Fire 5-Min L2 Swath 1km - Aqua	Land	Yes
MOD14A1	3	G	1000	Thermal Anomalies/Fire Daily L3 Global 1km - Terra	Land	Yes
MYD14A1	3	G	1000	Thermal Anomalies/Fire Daily L3 Global 1km - Aqua	Land	Yes
MOD14A2	3	G	1000	Thermal Anomalies/Fire 8-Day L3 Global 1km - Terra	Land	Yes
MYD14A2	3	G	1000	Thermal Anomalies/Fire 8-Day L3 Global 1km - Aqua	Land	Yes
MOD15A2	4	G	1000	Leaf Area Index/FPAR 8-Day L4 Global 1km - Terra	Land	Yes
MYD15A2	4	G	1000	Leaf Area Index/FPAR 8-Day L4 Global 1km - Aqua	Land	Yes
MOD17A2	4	G	1000	Gross Primary Productivity 8-Day L4 Global 1km - Terra	Land	Yes
MYD17A2	4	G	1000	Gross Primary Productivity 8-Day L4 Global 1km - Aqua	Land	Yes
MOD17A3	3	G	1000	Gross Primary Productivity Yearly L4 Global 1km - Terra	Land	Yes
MYD17A3	3	G	1000	Gross Primary Productivity Yearly L4 Global 1km - Aqua	Land	Yes
MOD43A1	4	G	500	BRDF/Albedo Model Parameters 16-Day L3 Global 500m - Terra	Land	Yes
MCD43A1	4	G	500	BRDF/Albedo Model Parameters 16-Day L3 Global 500m - Combined	Land	Yes
MOD43A2	4	G	500	BRDF/Albedo Quality 16-Day L3 Global 500m - Terra	Land	Yes
MCD43A2	4	G	500	BRDF/Albedo Quality 16-Day L3 Global 500m - Combined	Land	Yes
MOD43A3	4	G	500	Albedo 16-Day L3 Global 500m - Terra	Land	Yes
MCD43A3	4	G	500	Albedo 16-Day L3 Global 500m - Combined	Land	Yes
MOD43A4	4	G	500	Nadir BRDF-Adjusted Reflectance 16-Day L3 Global 500m - Terra	Land	Yes
MCD43A4	4	G	500	Nadir BRDF-Adjusted Reflectance 16-Day L3 Global 500m - Combined	Land	Yes
MOD43B1	3	G	1000	BRDF/Albedo Model Parameters 16-Day L3 Global 1km - Terra	Land	Yes
MCD43B1	3	G	1000	BRDF/Albedo Model Parameters 16-Day L3 Global 1km - Combined	Land	Yes
MOD43B2	4	G	1000	BRDF/Albedo Quality 16-Day L3 Global 1km - Terra	Land	Yes
MCD43B2	4	G	1000	BRDF/Albedo Quality 16-Day L3 Global 1km - Combined	Land	Yes
MOD43B3	3	G	1000	Albedo 16-Day L3 Global 1km - Terra	Land	Yes
MCD43B3	3	G	1000	Albedo 16-Day L3 Global 1km - Combined	Land	Yes
MOD43B4	3	G	1000	Nadir BRDF-Adjusted Reflectance 16-Day L3 Global 1km - Terra	Land	Yes
MCD43B4	3	G	1000	Nadir BRDF-Adjusted Reflectance 16-Day L3 Global 1km - Combined	Land	Yes
MOD43C1	3	G	0.05	BRDF/Albedo Parameters 16-Day L3 0.05Deg CMG - Terra	Land	Yes

The MODIS Conversion Toolkit User's Guide

MCD43C1	3	G	0.05	BRDF/Albedo Parameters 16-Day L3 0.05Deg CMG - Combined	Land	Yes
MOD43C2	4	G	0.05	BRDF/Albedo Snow-Free Quality 16-Day L3 Global 0.05Deg CMG - Terra	Land	Yes
MCD43C2	4	G	0.05	BRDF/Albedo Snow-Free Quality 16-Day L3 Global 0.05Deg CMG - Combined	Land	Yes
MOD43C3	3	G	0.05	Albedo 16-Day L3 Global 0.05Deg CMG - Terra	Land	Yes
MCD43C3	3	G	0.05	Albedo 16-Day L3 Global 0.05Deg CMG - Combined	Land	Yes
MOD43C4	4	G	0.05	Nadir BRDF-Adjusted Reflectance 16-Day L3 0.05Deg CMG - Terra	Land	Yes
MCD43C4	4	G	0.05	Nadir BRDF-Adjusted Reflectance 16-Day L3 0.05Deg CMG - Combined	Land	Yes
MOD44A	3	G	250	Vegetation Cover Conversion Quarterly L3 Global 250m	Land	Yes
MOD44B	3	G	500	Vegetation Continuous Fields Yearly L3 Global 500m	Land	Yes
MOD45A1	3	G	500	Burned Area Monthly L3 Global 500m - Terra	Land	Yes
MCD45A1	3	G	500	Burned Area Monthly L3 Global 500m - Combined	Land	Yes
MODMGGAD	2G	G	1000	Geolocation Angles Daily L2G Global 1km Day - Terra	Land	Yes
MYDMGGAD	2G	G	1000	Geolocation Angles Daily L2G Global 1km Day - Aqua	Land	Yes
MODPT1KD	2G	G	1000	Observation Pointers Daily L2G Global 1km Day - Terra	Land	Yes
MYDPT1KD	2G	G	1000	Observation Pointers Daily L2G Global 1km Day - Aqua	Land	Yes
MODPTHKM	2G	G	500	Observation Pointers Daily L2G Global 500m - Terra	Land	Yes
MYDPTHKM	2G	G	500	Observation Pointers Daily L2G Global 500m - Aqua	Land	Yes
MODPTQKM	2G	G	250	Observation Pointers Daily L2G Global 250m - Terra	Land	Yes
MYDPTQKM	2G	G	250	Observation Pointers Daily L2G Global 250m - Aqua	Land	Yes
MOD10A1	3	G	500	Snow Cover Daily L3 Global 500m SIN Grid - Terra	Cryosphere	Yes
MYD10A1	3	G	500	Snow Cover Daily L3 Global 500m SIN Grid - Aqua	Cryosphere	Yes
MOD10A2	3	G	500	Snow Cover 8-Day L3 Global 500m SIN Grid - Terra	Cryosphere	Yes
MYD10A2	3	G	500	Snow Cover 8-Day L3 Global 500m SIN Grid - Aqua	Cryosphere	Yes
MOD10C1	3	G	0.05	Snow Cover CMG Daily L3 Global Product 0.05Deg - Terra	Cryosphere	Yes
MYD10C1	3	G	0.05	Snow Cover CMG Daily L3 Global Product 0.05Deg - Aqua	Cryosphere	Yes
MOD10C2	3	G	0.05	Snow Cover 8-Day L3 Global 0.05Deg CMG - Terra	Cryosphere	Yes
MYD10C2	3	G	0.05	Snow Cover 8-Day L3 Global 0.05Deg CMG - Aqua	Cryosphere	Yes
MOD10CM	3	G	0.05	Snow Cover CMG Monthly L3 Global Product 0.05Deg - Terra	Cryosphere	Yes
MYD10CM	3	G	0.05	Snow Cover CMG Monthly L3 Global Product 0.05Deg - Aqua	Cryosphere	Yes
MOD10_L2	2	S	500	Snow Cover 5-Min L2 Swath 500m - Terra	Cryosphere	Yes
MYD10_L2	2	S	500	Snow Cover 5-Min L2 Swath 500m - Aqua	Cryosphere	Yes
MOD29	2	S	1000	Sea Ice Extent 5-Min L2 Swath 1km - Terra	Cryosphere	Yes
MYD29	2	S	1000	Sea Ice Extent 5-Min L2 Swath 1km - Aqua	Cryosphere	Yes
MOD29E1D	3	G	4000	Sea Ice Extent and IST Daily L3 Global 4km EASE-Grid Day - Terra	Cryosphere	Yes
MYD29E1D	3	G	4000	Sea Ice Extent and IST Daily L3 Global 4km EASE-Grid Day - Aqua	Cryosphere	Yes
MOD29P1D	3	G	1000	Sea Ice Extent Daily L3 Global 1km EASE-Grid Day - Terra	Cryosphere	Yes

The MODIS Conversion Toolkit User's Guide

MYD29P1D	3	G	1000	Sea Ice Extent Daily L3 Global 1km EASE-Grid Day - Aqua	Cryosphere	Yes
MOD29P1N	3	G	1000	Sea Ice Extent Daily L3 Global 1km EASE-Grid Night - Terra	Cryosphere	Yes
MYD29P1N	3	G	1000	Sea Ice Extent Daily L3 Global 1km EASE-Grid Night - Aqua	Cryosphere	Yes
OceanColor	1-3	S,G	1000 to 9000	More than 150 products can be generated through SeaDAS - Use EPOC	Ocean	Yes

